

ALUMINIUM TIPPING TRAILERS

Proudly built & manufactured in South Australia since 1986



CHASSIS AND T.O.A

Sliding & Fixed 'A' Trailers



Specifications

Model:	ST2/ST3
	Road Train & B Double Specs
Dimensions:	26' (7.9m) - 36' (10.9m) - Chassis
	30' (9.1m) - 36' (11m) - TOA
	Max width - 2500mm
	Height - 900mm - 2000mm
Construction:	Fabricated 'I' Beam
(Chassis)	16mm Top Flange
	20mm Bottom Flange
	5mm Webb - Grade 350 Steel
Construction:	100 x 100 x 6 RHS Subframe
(TOA)	100 x 75 x 6 RHS 2 piece Draw Arms
Tub Construction: Standard floor - 6mm Aluminium	
	Standard Wall - 5mm Aluminium
Skid Plate:	10mm thick with bolt in King Pin - Chassis
	16mm thick with bolt in King Pin - TOA
Braking System:	Knorr-Bremse Air Brake with Yard release
Landing Legs:	Jost T520 two speed Pad Feet
Axles:	York 5" round Spoke Hubs - Enclosed 'S' Cams
	Grease/Oil filled
	optional - 10 Stud & Disc (BPW, TMC)
Suspension:	York Tapered Bush cast with 8 Leaf Springs
	Optional: 3 Leaf Springs - Tecair Airbag
Hoist:	Binotto 4 & 5 stage 50 tonne
Tyre Carrier:	Dual bolt-on to underside
Lighting:	One piece wiring loom complete with
	HELLA LED jumbo rear and side lights
	to ADR requirements - 6mm wiring Road Train
Options:Roll Tarp, Extension Sides, Bagging Door	





34' x 6' T.O.A

Options:Roll Tarp, Extension Sides, Bagging Door Two Way Tailgate, Sub-door in front wall







FREIGHTMASTER SEMI TRAILERS PTY LTD 566 WATERLOO CORNER ROAD BURTON SA 5110 PHONE: (08) 8280 6475 FAX: (08) 8280 6772 www.freightmastertrailers.com.au Email: admin@freightmastertrailers.com.au

AGENT: